



SAFETY DATA SHEET

Issuing Date 21-Sept 2017

Revision Date 21-Sept 2017

Revision Number 1

1. IDENTIFICATION

GHS Product Identifier
WOODWELD – PART A

J-B Weld FG SKU Part Numbers Covered (Part A)
8250AUS, 8251AUS

Australia Contact Information

J-B Weld Distributor: HPP Lunds
Address: 1/195 Jackson Rd, Sunnybank Hills Qld 4109
Telephone: 1300 306 781

New Zealand Contact Information

J-B Weld Distributor: Griffith Equipment Ltd.
Address: 22-24 Olive Rd., Penrose, Auckland New Zealand 1061
Telephone: +64 9 5254577

Emergency Phone Number

For advice in an emergency, **In Australia contact** a Poisons Information Centre 13 11 26 or **In New Zealand contact** NZ Poisons Centre 0800 poison (0800 764 7667) or a doctor at once.

Company Name

J-B Weld Company LLC, USA

Address

1130 Como Street, Sulphur Springs TX 75482-4502, United States
Telephone: 011 903 885 7696

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonized System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Eye Damage/Irritation: Category 2A

Hazardous to the Aquatic Environment – Long-Term Hazard: Category 2

Sensitization – Skin: Category 1

Skin Corrosion/Irritation: Category 2

Signal Word(s)

WARNING

Hazard Statement(s)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statement(s)

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

Pictogram(s)

Exclamation mark, Environment



**Precautionary statement – Prevention**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

Precautionary statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	Proportion
Calcium carbonate	1317-65-3	30-60%
Bisphenol A, epichlorohydrin polymer	25068-38-6	10-<30%
Talc	14807-96-6	<10%
Fiberglass	65997-17-3	<10%
Oxirane, 2,2'-(1,4-butanediylbis(oxymethylene))bis-	2425-79-8	<10%
Bisphenol-F Epoxy Resin	9003-36-5	<10%
Crystalline Silica (Quartz)	14808-60-7	<1%
Ingredients determined not to be hazardous		Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek immediate medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 13 11 26) or a doctor at once.

Emergency Phone Number

For advice in an emergency, **In Australia contact** a Poisons Information Centre 13 11 26 or **In New Zealand contact** NZ Poisons Centre 0800 poison (0800 764 7667) or a doctor at once.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide, dry chemical or foam. Alcohol resistant foam is preferred. If not available normal foam can be used.

Unsuitable Extinguishing Media

Do not use water jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, including carbon monoxide and oxides of nitrogen.

Specific Hazards Arising from the Chemical

This product will burn if exposed to fire.

Hazchem Code

•3Z

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Increase ventilation. Wear appropriate personal protective equipment and clothing to prevent exposure. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the buildup of mists or vapours in the work atmosphere. Do not use near ignition sources. Do not pressurize, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene by washing hands prior to eating, drinking, smoking or using toilet facilities.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidizing agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.



For information on the design of the storeroom, reference should be made to Australian Standard AS1940 – The storage and handling of flammable and combustible liquids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Black Carbon
TWA: 3 mg/m³

Fiberglass (inhalable dust)
TWA: 2 mg/m³

Iron oxide fume (Fe₂O₃)(as Fe)
TWA: 5 mg/m³

Crystalline silica (quartz)
TWA: 0.1 mg/m³

Talc (containing no asbestos fibres)
TWA: 2.5 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Biological Limit Values

No biological limits allocated.

Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable mist/dust filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 – Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances, i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves – Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Form	Paste	Appearance	Paste contained in a metal tube. This tube is sold with a Part B that is also in a separate tube but are sold together in a set.
Color	Not available	Odor	Not available
Decomposition Temperature	Not available	Melting Point	Not available
Boiling Point	Not available	Solubility in Water	Not available
Specific Gravity	Not available	pH	Not available
Vapour Pressure	Not available	Vapour Density (Air=1)	Not available
Evaporation Rate	Not available	Odour Threshold	Not available
Viscosity	Not available	Volatile Component	Not available
Partition Coefficient: n-octanol / water	Not available	Flash Point	Not available
Flammability	Combustible	Auto-Ignition Temperature	Not available
Explosion Limit - Lower	Not available	Explosion Limit – Upper	Not available
Explosion properties	Not available	Oxidizing Properties	Not available

10. STABILITY AND REACTIVITY

Reactivity

Reacts with incompatible materials.

Chemical Stability

Stable under normal conditions of storage and handling.

Conditions to Avoid

Heat, open flames and other sources of ignition.

Incompatible materials

Strong oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes, including carbon monoxide, carbon dioxide and oxides of nitrogen.

Possibility of hazardous reactions

Reactions with incompatible materials

Hazardous Polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data available for this material.

Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system..



Skin

Causes skin irritation. May cause an allergic skin reaction. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory sensitization

Not expected to be a respiratory sensitizer.

Skin Sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

This product contains crystalline silica. No exposure to free respirable crystalline silica is anticipated during normal use of this product as silica is bound in the liquid/paste. It should be noted, however, that respirable crystalline silica has been listed as a Group 1 human carcinogen by the IARC. Inhalation of respirable silica may cause cancer, silicosis or other serious delayed lung injury. Grinding or machining of coated materials may release silica. Use approved dust respirator when grinding, sanding or machining the dried items.

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT-single exposure

Not expected to cause toxicity to a specific target organ.

STOT-repeated exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

Not expected to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Do not discharge this material into waterways, drains and sewers.



13. DISPOSAL CONSIDERATIONS

Disposal considerations

Dispose of waste according to applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

14. TRANSPORT INFORMATION

Transport Information

Road and Rail Transport:

This material is classified as Dangerous Goods Class 9 Miscellaneous Dangerous Goods.

Class 9: Miscellaneous substances Dangerous Goods are incompatible in a placard load with any of the following:

Class 1: Explosives (when the class 9 substance is a fire risk substance) Division 5.1: Oxidizing substances (when the class 9 substance is a fire risk substance) and Division 5.2: Organic peroxides (when the class 9 substance is a fire risk substance)

Note: Special Provision AU01:

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in: packagings that do not incorporate a receptacle exceeding 500 kg(L); or IBCs

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 9

UN no: 3082

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS BISPHENOL A, EPICHLOROHYDRIN POLYMER)(MARINE POLLUTANT)

Packing Group: III

EMS: F-A, S-F

Special Provisions: 274 335 969

Air Transport (ICAO/IATA)

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Class/Division: 9

UN No: 3082

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS BISPHENOL A, EPICHLOROHYDRIN POLYMER)

Packing Group: III

Packaging Instructions (passenger & cargo): 964

Packaging instructions (cargo only): 964

Hazard Label: Miscellaneous, Package Orientation

Special Provisions: A97, A158, A197

U.N. Number

3082

UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS BISPHENOL A, EPICHLOROHYDRIN POLYMER)

Transport hazard class(es)

9

Packing Group

III

Hazchem Code

•3Z

Special Precautions for User

Not available



IERG Number

47

IMDG Marine Pollutant

Yes

Transport in Bulk

Not available

15. REGULATORY INFORMATION**Regulatory Information**

Classified as Hazardous according to the Globally Harmonized System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule

S5

16. OTHER INFORMATION**Date of preparation or last revision of SDS**

SDS Created: January 2017

References

- Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
- Standard for the Uniform Scheduling of Medicines and Poisons.
- Australian Code for the Transport of Dangerous Goods by Road & Rail.
- Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
- Workplace exposure standards for airborne contaminants.
- Adopted biological exposure determinants. American Conference of Industrial Hygienists (ACGIH).
- Globally Harmonized System of classification and labelling of chemicals.

END OF SDS

Copyright in the source code of the HTML, PDF, XMI, XFO and any other electronic files rendered by an infosafe system for infosafe SDS displayed is the intellectual property of J-B Weld Company LLC USA.

Copyright in the layout, presentation and appearance of each infosafe SDS displayed is the intellectual property of J-B Weld Company LLC USA.

The compilation of SDS's displayed is the intellectual property of J-B Weld Company LLC USA.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or license or for inclusion as part of a collection of SDS without the express written consent of J-B Weld Company LLC USA.

